



HES

5000/5200 - Series Electric Strike

Features:

- In-frame horizontal adjustability
- Heavy duty - for use with up to 3/4" latchbolts
- Dual voltage 12 or 24 VDC/VAC
- Field selectable fail secure / fail safe
- Forcing strength rating 1,500 lbs
- Dynamic force rating 70ft-lbs
- Endurance rating 250,000 cycles (factory tested to over 1,000,000)
- Internally mounted solenoid
- Non-handed
- Trim enhancer (goof plate) included
- Five year warranty
- Strike Body Depth 1-3/16"



5200 series
The convenient adjustable solution.

*available february 2005

- UL T034 burglary rated
- field selectable (12 or 24VDC)
- field selectable (fail secure / fail safe)
- grade 1
- cylindrical locksets
- specialty locksets

- Dual voltage 12 or 24 VDC/VAC
- Field selectable fail secure / fail safe
- Forcing strength rating 1,500 lbs
- Dynamic force rating 70ft-lbs
- Endurance rating 250,000 cycles (factory tested to over 1,000,000)
- Internally mounted solenoid
- Non-handed
- Trim enhancer (goof plate) included
- Five year warranty
- Strike Body Depth 1-1/16"



5000 series
The grade 1 low profile solution

- cylindrical locksets
- grade 1
- field selectable (12 or 24VDC)
- field selectable (fail secure / fail safe)
- UL T034 burglary rated

Stocked Product

- 5000 and 5200 finish: 630
- 501A face plate finish: 613, 630
- 503 face plate finish: 613, 630
- 501 face plate finish 630



503

For use with cylindrical locksets. For use with latchbolts up to 1/2" throw. Includes universal mounting tabs. Aluminum frames.



501

Square corner, flat face plate. For use with cylindrical locksets in ANSI metal jambs. For use with latch bolts up to 1/2" throw



501A

Radius corner, flat face plate. For use with cylindrical locksets. For use with latch bolts up to 1/2" throw includes universal mounting tabs. Aluminum frames