

Coordinators - Bar Coordinators and Filler Bars

COR Series Bar Coordinators



- The COR Series Coordinators are designed for use on pairs of doors when one door needs to close before the other.
- All COR units function easily. The active door lever, located nearest to the active stop, holds the active door open until the trigger mechanism is released by the closing of the inactive leaf.
- All COR units are equipped with an override feature which allows the active door to close under extreme pressure.
- All COR units are compatible with Flush Bolts.
- The COR Series is available in five sizes for variable door opening widths.
- The COR Series does not cover the entire length of the stop, so a filler bar can be provided to maintain architecturally clean lines.
- COR Series Coordinator Channels and fillers are made of aluminum and are normally furnished in a US28 finish. Also available in US26D, and 315AN (Black).
- Meets ANSI/BHMA A156.3, Type 21A.
- UL Listed for installation on labeled frame.
- Optional Filler Bars: FL20, FL32 and FL44, available to maintain clean line.
- Optional Mounting Brackets available: MB1, MB2, MB1F, MB2F, MB3F, MB1V, MB2V, and MB3V for other stop applied hardware.

Dimensions: 1-5/8" Wide x 5/8" Deep x Ordered Length

For Openings Where Doors Are Same Size

Coordinator Number	Length of Channel	For Opening Widths	Common Applications
COR32	32"	34" - 52"	Pair of 2'0" Doors
COR42	42"	52" - 72"	Pair of 2'6" Doors
COR52	52"	62" - 92"	Pair of 3'0" Doors
COR60	60"	70" - 108"	Pair of 3'6" Doors
COR72	72"	84" - 132"	Pair of 4'0" Doors

For Openings Where Doors Are Unequal Size

The coordinator length should equal the active door width plus approximately 1/2 the inactive door width. The coordinator must be 6" longer than the active door width and shorter than the overall frame opening between stops.

FL Series Filler Bars

- The FL Filler Bars are available in three sizes for variable frame openings.
- FL Filler Bars are made of aluminum and are normally furnished in a US28 finish. Also available in US26D and 315AN (Black).
- FL Filler Bars are field sized to frame opening.



Filler Bar Number	Length
FL20	20"
FL32	32"
FL44	44"

Dimensions: 1-5/8" Wide x 5/8" Deep x Ordered Length